NSN 5305-00-245-8823

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-245-8823 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.381 inches and 0.448 inches **Fastener Length:** Between 0.703 inches and 0.750 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.377 inches and 0.381 inches **Head Height:** Between 0.044 inches and 0.046 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.302 inches and 0.322 inches Thready Qty Per Inch (tpi): 32 Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** 100.0 degrees **Special Features:** Furnished with one rubber o-ring Material: Steel comp 8735 or steel comp 4130 or steel comp 4140 or steel comp 4340 or steel comp 8740 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a

Unit Of Measure:

NSN 5305-00-245-8823

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0