NSN 5305-00-246-6400

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-246-6400 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.171 inches **Fastener Length:** 0.562 inches **Head Style:** Knurled no. 1 **Head Diameter:** 0.312 inches **Head Height:** 0.125 inches **First Diameter From Head:** Between 0.136 inches and 0.138 inches **Second Diameter From Head:** Between 0.105 inches and 0.111 inches Third Diameter From Head: Between 0.136 inches and 0.138 inches **Fourth Diameter From Head:** 0.093 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.266 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.297 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 0.329 inches Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: 0.391 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 4

Material:

Steel comp 303

Material Specification:

Qq-s-764 federal specification single material response

NSN 5305-00-246-6400

Externally Relieved Body Screw - Page 2 of 2



| Thread Series Designator: |
|---------------------------|
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A003b0