## NSN 5305-00-247-9181

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-247-9181 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.310 inches and 0.340 inches **Fastener Length:** Between 0.450 inches and 0.490 inches **Head Style:** Hexagon **Head Height:** Between 0.020 inches and 0.040 inches Width Between Flats: Between 0.240 inches and 0.260 inches **Shoulder Diameter:** 0.206 inches first shoulder and 0.208 inches first shoulder **Shoulder Length:** 0.140 inches first shoulder and 0.150 inches first shoulder **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 **Shoulder Shape:** Round first shoulder **Special Features:** 0.090 in. Thd relief Material: Steel comp 303 **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072, finish e300 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

No

## NSN 5305-00-247-9181

Shoulder Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.