

View Online at <https://aerobasegroup.com/nsn/5305-00-251-4003>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.260 inches and 0.341 inches

Fastener Length:

Between 0.344 inches and 0.375 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.181 inches and 0.199 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.099 inches

Thready Qty Per Inch (tpi):

48

Min. Tensile Strength (psi):

80000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Screw Material:

Steel comp 321 or steel comp 347 or steel comp 302 or steel comp 303

Screw Material Specification:

Qq-s-763 federal specification 1st material response or qq-s-763 federal specification 2nd material response or mil-s-7720jbeqq-s-763 military specification 3rd material response

Screw Surface Treatment:

Passivate

Screw Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-7720jbeqq-s-763 spec.