NSN 5305-00-251-4003



Machine Screw - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5305-00-251-4003 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.260 inches and 0.341 inches **Fastener Length:** Between 0.344 inches and 0.375 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.181 inches and 0.199 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.099 inches Thready Qty Per Inch (tpi): 48 Min. Tensile Strength (psi): 80000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Steel comp 321 or steel comp 347 or steel comp 302 or steel comp 303 **Screw Material Specification:** Qq-s-763 federal specification 1st material response or qq-s-763 federal specification 2nd material response or mil-s-7720jbeqq-s-763 military specification 3rd material response **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

Fiig: A500d0

No

Mil-std (military Standard):

Mil-s-7720jbeqq-s-763 spec.