NSN 5305-00-252-9499

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-252-9499

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.378 inches and 0.428 inches
Fastener Length:
Between 1.263 inches and 1.293 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.355 inches and 0.397 inches
Shoulder Diameter:
0.264 inches first shoulder and 0.265 inches first shoulder
Shoulder Length:
0.802 inches first shoulder and 0.822 inches first shoulder
Internal Drive Style:
High-torque
Thread Diameter:
0.250 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Shoulder Shape:
Round first shoulder
Material:
Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, cl 2 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:

NSN 5305-00-252-9499

Shoulder Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

