NSN 5305-00-252-9683

Machine Screw - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5305-00-252-9683



Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.407 inches and 0.500 inches

Fastener Length:

Between 0.469 inches and 0.500 inches

Head Style:

Pan

Head Diameter:

Between 0.357 inches and 0.373 inches

Head Height:

Between 0.122 inches and 0.133 inches

Internal Drive Style:

Cross recess type 1

End Application:

Trlr, cargo, 3/4t, 2-whl, tam d08607; communicationsprogram, combat theater (tri-tac)4781; 485I tacs; aircraft, hercules c-130

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

55000 pounds per square inch

Screw Material:

Copper alloy

Screw Material Specification:

Qq-b-613 federal specification single material response or qq-b-626 federal specification single material response or qq-w-321 federal

specification single material response

Screw Surface Treatment:

Nickel

Screw Surface Treatment Specification:

Qq-n-290, cl 1, gr g federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

- Fiig:
- A500d0