NSN 5305-00-252-9683

Machine Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-252-9683 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.407 inches and 0.500 inches **Fastener Length:** Between 0.469 inches and 0.500 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **Internal Drive Style:** Cross recess type 1 **End Application:** Trlr, cargo, 3/4t, 2-whl, tam d08607; communicationsprogram, combat theater (tri-tac)4781; 485l tacs; aircraft, hercules c-130 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 55000 pounds per square inch **Screw Material:** Copper alloy **Screw Material Specification:** Qq-b-613 federal specification single material response or qq-b-626 federal specification single material response or qq-w-321 federal specification single material response **Screw Surface Treatment:** Nickel **Screw Surface Treatment Specification:** Qq-n-290, cl 1, gr g federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

No

Fiig:

A500d0

Demilitarization: