NSN 5305-00-253-0472

Hexagon Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-253-0472 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 1.250 inches **Fastener Length:** Between 1.625 inches and 1.750 inches **Head Style:** Hexagon **Head Height:** Between 0.302 inches and 0.323 inches Width Between Flats: Between 0.736 inches and 0.750 inches **Hole Diameter:** 0.094 inches **Thread Diameter:** 0.500 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 70000 pounds per square inch Hardness Rating: 235.0 brinell standard Minimum Yield Strength: 40000 pounds per square inch **Hole Configuration Style:** Hexagon flats Material: Steel comp 403 or steel comp 405 or steel comp 410 or steel comp 414 or steel comp 416 or steel comp 416se or steel comp 420 or steel comp 430 or steel comp 430f or steel comp 430fse or steel comp 431 or steel comp 440a or steel comp 440b or steel comp 440c or steel comp 446 **Surface Treatment: Passivate**

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unf

Specification Or Standard:

2 type and 10p style

NSN 5305-00-253-0472

Hexagon Head Cap Screw - Page 2 of 2



		fe:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0