NSN 5305-00-253-1720

Setscrew - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-253-1720
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.235 inches and 0.255 inches
Fastener Length:
Between 0.390 inches and 0.410 inches
Head Style:
Hexagon
Head Height:
Between 0.109 inches and 0.141 inches
Width Between Flats:
Between 0.365 inches and 0.377 inches
Hole Diameter:
0.046 inches
Point Style:
Full dog
Internal Drive Style:
W/o internal drive
Thread Diameter:
0.190 inches
Hole Quantity:
1
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
32
Hole Configuration Style:
Hexagon longitudinal hole
Material:
Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740
Material Specification:
Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military
specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material
response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416, type 2, class 1 federal specification single treatment response or qq-p-416, type 3, class 1 federal specification single treatment
response
Thread Series Designator:
Unf

. . .

Shelf Life:

NSN 5305-00-253-1720

Setscrew - Page 2 of 2



U	n	it	Of	Μe	eas	ur	e:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.