## NSN 5305-00-253-1720

Setscrew - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-253-1720



## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

Between 0.235 inches and 0.255 inches

### Fastener Length:

Between 0.390 inches and 0.410 inches

#### Head Style:

Hexagon

Head Height:

Between 0.109 inches and 0.141 inches

### Width Between Flats:

Between 0.365 inches and 0.377 inches

### Hole Diameter:

## 0.046 inches

Point Style:

Full dog

## Internal Drive Style:

W/o internal drive

## **Thread Diameter:**

0.190 inches

### Hole Quantity:

1

## Hole Type:

Drilled

## Thready Qty Per Inch (tpi):

32

## Hole Configuration Style:

Hexagon longitudinal hole

## Material:

Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740

## **Material Specification:**

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response

## Surface Treatment:

Cadmium

## Surface Treatment Specification:

Qq-p-416, type 2, class 1 federal specification single treatment response or qq-p-416, type 3, class 1 federal specification single treatment response

## **Thread Series Designator:**

Unf

NI/o

## Shelf Life:

# NSN 5305-00-253-1720

Setscrew - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.

