

View Online at <https://aerobasegroup.com/nsn/5305-00-253-4107>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.065 inches and 0.096 inches

**Fastener Length:**

Between 0.090 inches and 0.096 inches

**Head Style:**

Binding

**Head Diameter:**

Between 0.110 inches and 0.116 inches

**Head Height:**

Between 0.018 inches and 0.022 inches

**Internal Drive Style:**

Slot

**End Application:**

W/s: helicopter, advance attack, ah-1w; aircraft, awacs, e-3a; helicopter, seahawk, h-60; aircraft, galaxy c-5; aircraft, tomcat f-14; aircraft, viking s-3b; helicopter, chinook, ch-47; helicopter, carrier based asw, sh-60f; helicopter, search and rescue, hh-60h; helicopter, iroquois uh-1

**Thread Diameter:**

0.060 inches

**Thready Qty Per Inch (tpi):**

80

**Screw Material:**

Copper alloy 342

**Screw Surface Treatment:**

Oxide

**Screw Surface Treatment Specification:**

Mil-f-495, cl 1 military specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0

**Mil-std (military Standard):**

Mil-f-495 spec.