

View Online at <https://aerobasegroup.com/nsn/5305-00-253-4107>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.065 inches and 0.096 inches

Fastener Length:

Between 0.090 inches and 0.096 inches

Head Style:

Binding

Head Diameter:

Between 0.110 inches and 0.116 inches

Head Height:

Between 0.018 inches and 0.022 inches

Internal Drive Style:

Slot

End Application:

W/s: helicopter, advance attack, ah-1w; aircraft, awacs, e-3a; helicopter, seahawk, h-60; aircraft, galaxy c-5; aircraft, tomcat f-14; aircraft, viking s-3b; helicopter, chinook, ch-47; helicopter, carrier based asw, sh-60f; helicopter, search and rescue, hh-60h; helicopter, iroquois uh-1

Thread Diameter:

0.060 inches

Thready Qty Per Inch (tpi):

80

Screw Material:

Copper alloy 342

Screw Surface Treatment:

Oxide

Screw Surface Treatment Specification:

Mil-f-495, cl 1 military specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-f-495 spec.