

View Online at <https://aerobasegroup.com/nsn/5305-00-253-5607>

**Fastener Length:**

0.188 inches

**Head Style:**

Round

**Head Diameter:**

Between 0.118 inches and 0.127 inches

**Head Height:**

Between 0.041 inches and 0.049 inches

**Pilot Diameter:**

Between 0.060 inches and 0.063 inches

**Pilot Length:**

0.047 inches

**End Application:**

Communications terminal, satellite an/gsc-3 (v)1; engine, aircraft tf33-p-3/5/9 (c/ec-135, b-52h); trainer, b-1b aircraft; systems, jp-5 aviation fuels; airborne mobile dir air spt ctl (2id, 02m jul83)(an/uyq-3a); close in weapon system (ciws-phalanx); engine, aircraft tf33-pw-102 (c135e, ec-135h/k/p); aircraft, (ac-130h, mc-130h, ec-130e, hc-130); support equipment, b-1 aircraft; gun, 5-in./54 cal, mk-54; guided missile launching sys

**Features Provided:**

Casehardened

**Nonmachine Thread Style:**

Drive screw (type u)

**Nonmachine Thread Diameter:**

0.073 inches

**Material:**

Steel

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 3 federal specification all treatment responses

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0