

View Online at <https://aerobasegroup.com/nsn/5305-00-253-5607>

Fastener Length:

0.188 inches

Head Style:

Round

Head Diameter:

Between 0.118 inches and 0.127 inches

Head Height:

Between 0.041 inches and 0.049 inches

Pilot Diameter:

Between 0.060 inches and 0.063 inches

Pilot Length:

0.047 inches

End Application:

Communications terminal, satellite an/gsc-3 (v)1; engine, aircraft tf33-p-3/5/9 (c/ec-135, b-52h); trainer, b-1b aircraft; systems, jp-5 aviation fuels; airborne mobile dir air spt ctl (2id, 02m jul83)(an/uyq-3a); close in weapon system (ciws-phalanx); engine, aircraft tf33-pw-102 (c135e, ec-135h/k/p); aircraft, (ac-130h, mc-130h, ec-130e, hc-130); support equipment, b-1 aircraft; gun, 5-in./54 cal, mk-54; guided missile launching sys

Features Provided:

Casehardened

Nonmachine Thread Style:

Drive screw (type u)

Nonmachine Thread Diameter:

0.073 inches

Material:

Steel

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 3 federal specification all treatment responses

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0