

View Online at <https://aerobasegroup.com/nsn/5305-00-253-5609>

Fastener Length:

Between 0.109 inches and 0.141 inches

Head Style:

Round

Head Diameter:

Between 0.146 inches and 0.162 inches

Head Height:

Between 0.059 inches and 0.069 inches

Pilot Diameter:

Between 0.080 inches and 0.083 inches

Pilot Length:

0.047 inches

End Application:

Aircraft, (ac-130h, mc-130h, ec-0130e, hc-130); airborne mobile dir air spt ctl (2id), (02m jul83)(an/uyq-3a); support equipment, b-1 aircraft; missile, all-weather anti-ship, harpoon (agm-84); compressor, reciprocating m4; radar set, an/tpn-18; engine, aircraft tf33-pw-102 (c-135e, ec-135h/k/p); close in weapon system (ciws-phlanx); aircraft, awacs, e-3a; engine, aircraft tf33-p-3/5/9 (c/ec-135, b-52h); sturgeon class ssn (637)

Features Provided:

Casehardened

Nonmachine Thread Style:

Drive screw (type u)

Nonmachine Thread Diameter:

0.098 inches

Material:

Steel

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 3 federal specification all treatment responses

Specification Or Standard:

U type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0