

View Online at <https://aerobasegroup.com/nsn/5305-00-253-5614>

**Fastener Length:**

Between 0.172 inches and 0.204 inches

**Head Style:**

Round

**Head Diameter:**

Between 0.193 inches and 0.211 inches

**Head Height:**

Between 0.075 inches and 0.086 inches

**Pilot Diameter:**

Between 0.092 inches and 0.096 inches

**Pilot Length:**

0.047 inches

**End Application:**

W/s: vehicle, aircraft refueler r-14; aircraft, galaxy c-5; aircraft, (ac-130h, mc-130h, ec-130e, hc-130); support equipment, b-1 aircraft; missile, air-to-air, phoenix (aim-54); torpedo, mk 48; missile, all-weather anti-ship, harpoon (agm-84); close in weapon system (ciws-phalanx); missile air-to-air, sparrow (aim-7); ground mobile force satellite comm term (an/tsc-85a); 2320-01-097-0260 hemtt (heavy expanded mobility tactical trucks)

**Features Provided:**

Casehardened

**Nonmachine Thread Style:**

Drive screw (type u)

**Nonmachine Thread Diameter:**

0.114 inches

**Material:**

Steel

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 3 federal specification all treatment responses

**Specification Or Standard:**

U type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0