

View Online at <https://aerobasegroup.com/nsn/5305-00-253-5614>

Fastener Length:

Between 0.172 inches and 0.204 inches

Head Style:

Round

Head Diameter:

Between 0.193 inches and 0.211 inches

Head Height:

Between 0.075 inches and 0.086 inches

Pilot Diameter:

Between 0.092 inches and 0.096 inches

Pilot Length:

0.047 inches

End Application:

W/s: vehicle, aircraft refueler r-14; aircraft, galaxy c-5; aircraft, (ac-130h, mc-130h, ec-130e, hc-130); support equipment, b-1 aircraft; missile, air-to-air, phoenix (aim-54); torpedo, mk 48; missile, all-weather anti-ship, harpoon (agm-84); close in weapon system (ciws-phalanx); missile air-to-air, sparrow (aim-7); ground mobile force satellite comm term (an/tsc-85a); 2320-01-097-0260 hemtt (heavy expanded mobility tactical trucks)

Features Provided:

Casehardened

Nonmachine Thread Style:

Drive screw (type u)

Nonmachine Thread Diameter:

0.114 inches

Material:

Steel

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 3 federal specification all treatment responses

Specification Or Standard:

U type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0