NSN 5305-00-253-7845

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-253-7845

Thread Class:					
3a					
Thread Direction:					
Right-hand					
Thread Length:					
Between 0.133 inches and 0.188 inches					
Fastener Length:					
Between 0.158 inches and 0.188 inches					
Head Style:					
Flat chamfer					
Head Diameter:					
Between 0.091 inches and 0.096 inches					
Head Height:					
Between 0.057 inches and 0.060 inches					
Internal Drive Style:					
Hexagon					
Thread Diameter:					
0.060 inches					
Width Across Flats:					
Between 0.050 inches and 0.051 inches					
Thready Qty Per Inch (tpi):					
80					
Min. Tensile Strength (psi):					
80000 pounds per square inch					
Hardness Rating:					
80.0 rockwell b					
Minimum Yield Strength:					
30000 pounds per square inch					
Material:					
Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316					
Material Specification:					
66 federal standard all material responses					
Surface Treatment:					
Passivate					
Surface Treatment Specification:					
Qq-p-35 federal specification single treatment response					
Thread Series Designator:					
Unrf					
Specification Data:					
80205-nas1351 professional/industrial association standard					
Shelf Life:					
N/a					

NSN 5305-00-253-7845

Socket Head Cap Screw - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0