NSN 5305-00-253-9885

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-253-9885 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.475 inches and 0.525 inches **Fastener Length:** Between 1.235 inches and 1.265 inches **Head Style:** Bevel-conical **Head Diameter:** Between 0.428 inches and 0.438 inches **Head Height:** Between 0.240 inches and 0.260 inches **Shoulder Diameter:** 0.2797 inches first shoulder and 0.2807 inches first shoulder **Shoulder Length:** 0.740 inches first shoulder and 0.760 inches first shoulder **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: Between 0.188 inches and 0.190 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** 34.0 rockwell c and 40.0 rockwell c **Shoulder Shape:** Round first shoulder Material: Steel **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416 type2 class3 federal specification single treatment response **Thread Series Designator:**

Unf

Shelf Life:

N/a

NSN 5305-00-253-9885

Shoulder Screw - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0