

View Online at <https://aerobasegroup.com/nsn/5305-00-255-1474>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.245 inches

**Fastener Length:**

Between 0.350 inches and 0.380 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.256 inches and 0.270 inches

**Head Height:**

Between 0.087 inches and 0.097 inches

**First Diameter From Head:**

Between 0.096 inches and 0.100 inches

**Second Diameter From Head:**

Between 0.074 inches and 0.076 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.060 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

0.120 inches

**Internal Drive Style:**

Cross recess type 1

**End Application:**

An/alq-94/137 common

**Thread Diameter:**

0.138 inches

**Thready Qty Per Inch (tpi):**

32

**Externally Relieved Body Diameter Quantity:**

2

**Special Features:**

With cone type point

**Material:**

Stainless steel

**Material Specification:**

Qq-s-763 federal specification single material response or 66 federal standard single material response

**Surface Treatment:**

Oxide

**Surface Treatment Specification:**

Mil-c-13924 cl 2 or 4 military specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-13924 spec.