NSN 5305-00-255-1474

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-255-1474 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.245 inches **Fastener Length:** Between 0.350 inches and 0.380 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches **First Diameter From Head:** Between 0.096 inches and 0.100 inches **Second Diameter From Head:** Between 0.074 inches and 0.076 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.060 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.120 inches **Internal Drive Style:** Cross recess type 1 **End Application:** An/alq-94/137 common **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity: Special Features:** With cone type point Material: Stainless steel **Material Specification:** Qq-s-763 federal specification single material response or 66 federal standard single material response **Surface Treatment:**

Oxide

Surface Treatment Specification:

Mil-c-13924 cl 2 or 4 military specification single treatment response

NSN 5305-00-255-1474

Externally Relieved Body Screw - Page 2 of 2



Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0
Mil-std (military Standard):

Mil-c-13924 spec.