## NSN 5305-00-256-1382

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-256-1382 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.170 inches and 0.190 inches **Fastener Length:** Between 0.427 inches and 0.447 inches **Head Style:** Pan **Head Diameter:** Between 0.209 inches and 0.219 inches **Head Height:** Between 0.070 inches and 0.080 inches **First Diameter From Head:** Between 0.078 inches and 0.082 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.357 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Material Specification:** 66 federal standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072, no.E300 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

## NSN 5305-00-256-1382

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.