Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-256-7282

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.533 inches and 0.625 inches
Fastener Length:
Between 0.595 inches and 0.625 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.218 inches and 0.226 inches
Head Height:
Between 0.134 inches and 0.138 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.138 inches
Width Across Flats:
Between 0.109 inches and 0.111 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
80000 pounds per square inch
Hardness Rating:
80.0 rockwell b
Minimum Yield Strength:
30000 pounds per square inch
Special Features:
Finish color black
Material:
Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316
Material Specification:
66 federal standard all material responses Surface Treatment:
Oxide Surface Treatment Specification:
Surface Treatment Specification: Mil-c-13924, cl 4 military specification single treatment response
Thread Series Designator:
Unc
Specification Or Standard:
6 type

NSN 5305-00-256-7282

Socket Head Cap Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.

