

View Online at <https://aerobasegroup.com/nsn/5305-00-256-8409>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.670 inches and 0.750 inches

Fastener Length:

Between 0.720 inches and 0.750 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.218 inches and 0.226 inches

Head Height:

Between 0.134 inches and 0.138 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.138 inches

Width Across Flats:

Between 0.109 inches and 0.111 inches

Thready Qty Per Inch (tpi):

40

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 45.0 rockwell c

Minimum Yield Strength:

155000 pounds per square inch

Material:

Steel

Material Specification:

66 federal standard single material response

Surface Treatment:

Oxide

Surface Treatment Specification:

Mil-c-13924, cl 1 military specification single treatment response

Thread Series Designator:

Unrf

Specification Data:

80205-nas1351 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.