
NSN 5305-00-257-0903

Setscrew - Page 1 of 2





Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.250 inches

Fastener Length:

Between 0.219 inches and 0.250 inches

Head Style:

Square

Head Height:

Between 0.178 inches and 0.196 inches

Width Between Flats:

Between 0.241 inches and 0.250 inches

Point Style:

Oval

Internal Drive Style:

W/o internal drive

Thread Diameter:

0.250 inches

Features Provided:

Casehardened

Thready Qty Per Inch (tpi):

20

Hardness Rating:

30.0 rockwell c and 37.0 rockwell c

Material:

Steel comp 1010 or steel comp 1011 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1022 or steel comp 1212 or steel comp 1213 or steel comp 1137

Material Specification:

66 federal standard all material responses

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 3 federal specification all treatment responses

Thread Series Designator:

Unc

Specification Or Standard:

1 type and 3 style

Shelf Life:

N/a

Unit Of Measure:

NSN 5305-00-257-0903

Setscrew - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

