NSN 5305-00-257-5584

Setscrew - Page 1 of 2

Between 0.566 inches and 0.687 inches

Thread Class:

Right-hand

Thread Length:

Thread Direction:

Fastener Length:

За



View Online at https://aerobasegroup.com/nsn/5305-00-257-5584

Between 0.687 inches and 0.717 inches	
Head Style:	
Hexagon	
Head Height:	
Between 0.140 inches and 0.172 inches	
Width Between Flats:	
Between 0.428 inches and 0.440 inches	
Hole Diameter:	
0.051 inches	
Point Length:	
Between 0.130 inches and 0.150 inches	
Point Diameter:	
Between 0.165 inches and 0.185 inches	
Point Style:	
Dog	
Internal Drive Style:	
W/o internal drive	
Thread Diameter:	
0.250 inches	
Hole Quantity:	
1	
Hole Type:	
Drilled	
Thready Qty Per Inch (tpi):	
28	
Min. Tensile Strength (psi):	
220000 pounds per square inch	
Hardness Rating:	
46.0 rockwell c and 48.0 rockwell c	
Hole Configuration Style:	
Hexagon corners	
Material:	
Steel comp 4340	
Material Specification:	
Mil-s-5000 military specification single material	response

NSN 5305-00-257-5584

Setscrew - Page 2 of 2

Mil-s-5000 spec.



Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416 type 2 cl 2 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0
Mil-std (military Standard):