

View Online at <https://aerobasegroup.com/nsn/5305-00-257-5584>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.566 inches and 0.687 inches

**Fastener Length:**

Between 0.687 inches and 0.717 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.140 inches and 0.172 inches

**Width Between Flats:**

Between 0.428 inches and 0.440 inches

**Hole Diameter:**

0.051 inches

**Point Length:**

Between 0.130 inches and 0.150 inches

**Point Diameter:**

Between 0.165 inches and 0.185 inches

**Point Style:**

Dog

**Internal Drive Style:**

W/o internal drive

**Thread Diameter:**

0.250 inches

**Hole Quantity:**

1

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Hardness Rating:**

46.0 rockwell c and 48.0 rockwell c

**Hole Configuration Style:**

Hexagon corners

**Material:**

Steel comp 4340

**Material Specification:**

Mil-s-5000 military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5000 spec.