NSN 5305-00-257-5585

Setscrew - Page 1 of 2

Between 1.426 inches and 1.547 inches

Thread Class:

Right-hand

Thread Length:

Thread Direction:

Fastener Length:

За



View Online at https://aerobasegroup.com/nsn/5305-00-257-5585

Between 1.687 inches and 1.717 inches
Head Style:
Hexagon
Head Height:
Between 0.140 inches and 0.172 inches
Width Between Flats:
Between 0.428 inches and 0.440 inches
Hole Diameter:
0.051 inches
Point Length:
Between 0.130 inches and 0.150 inches
Point Diameter:
Between 0.165 inches and 0.185 inches
Point Style:
Dog
Internal Drive Style:
W/o internal drive
Thread Diameter:
0.250 inches
Hole Quantity:
Hole Quantity:
•
1
1 Hole Type:
1 Hole Type: Drilled
1 Hole Type: Drilled Thready Qty Per Inch (tpi):
1 Hole Type: Drilled Thready Qty Per Inch (tpi): 28
Hole Type: Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi):
Hole Type: Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 220000 pounds per square inch
Hole Type: Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating:
Hole Type: Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 48.0 rockwell c
Hole Type: Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 48.0 rockwell c Hole Configuration Style:
Hole Type: Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 48.0 rockwell c Hole Configuration Style: Hexagon corners
Hole Type: Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 48.0 rockwell c Hole Configuration Style: Hexagon corners Material:
Hole Type: Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 48.0 rockwell c Hole Configuration Style: Hexagon corners Material: Steel comp 4340
Hole Type: Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 48.0 rockwell c Hole Configuration Style: Hexagon corners Material: Steel comp 4340 Material Specification:
Hole Type: Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 48.0 rockwell c Hole Configuration Style: Hexagon corners Material: Steel comp 4340 Material Specification:

NSN 5305-00-257-5585

Setscrew - Page 2 of 2

Mil-std (military Standard):

Mil-s-5000 spec.



Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416 type 2 cl 2 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0