NSN 5305-00-259-1107

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-259-1107 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.346 inches and 0.448 inches **Fastener Length:** Between 0.470 inches and 0.500 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.267 inches and 0.279 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c **Countersink Angle:** 100.0 degrees **Screw Material:** Steel comp 4037 or steel comp 8630 **Screw Material Specification:** Ams 6300 assn standard 1st material response or mil-s-6050 military specification 2nd material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification all treatment responses **Special Features:** Color gray no. 36307 fed-std-595 **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-00-259-1107

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-s-6050 spec.