NSN 5305-00-268-1947

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-268-1947 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.156 inches **Fastener Length:** 0.620 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.340 inches and 0.385 inches First Diameter From Head: 0.156 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.348 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 80000 pounds per square inch **Countersink Angle:** Between 80.0 degrees and 82.0 degrees **Externally Relieved Body Diameter Quantity:** Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072 finish e300 military specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5305-00-268-1947

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.