NSN 5305-00-269-3232

Hexagon Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-269-3232 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.562 inches **Fastener Length:** 0.562 inches **Head Style:** Hexagon **Head Height:** Between 0.226 inches and 0.243 inches Width Between Flats: Between 0.551 inches and 0.562 inches **End Application:** Mrap buffalo mk2a2 **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 150000 pounds per square inch **Hardness Rating:** 32.0 rockwell c and 38.0 rockwell c Minimum Yield Strength: 120000 pounds per square inch Material: Steel **Material Specification:** Sae j429 grade 8 assn standard single material response **Surface Treatment:** Zinc and chromate **Surface Treatment Specification:** Astm b633 type 2 sc 3 assn standard single treatment response **Thread Series Designator:** Unf **Specification Or Standard:** 2 type and 10p style and 8 grade Shelf Life: N/a

Unit Of Measure:

NSN 5305-00-269-3232

Hexagon Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0