# NSN 5305-00-271-3493

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-271-3493



# Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

#### Thread Length:

Between 0.346 inches and 0.485 inches

#### Fastener Length:

Between 1.954 inches and 2.001 inches

#### Head Style:

Round

#### Head Diameter:

Between 0.309 inches and 0.331 inches

#### **Head Height:**

Between 0.088 inches and 0.102 inches

#### Internal Drive Style:

Cross recess type 1

## Thread Diameter:

0.164 inches

### Thready Qty Per Inch (tpi):

32

#### Min. Tensile Strength (psi):

125000 pounds per square inch

#### Hardness Rating:

Between 26.0 rockwell c and 32.0 rockwell c

#### Screw Material:

Steel comp 8630

#### **Screw Material Specification:**

Mil-s-6050 military specification single material response or an-s-9 military standard single material response

#### Screw Surface Treatment:

Cadmium

#### Screw Surface Treatment Specification:

Qq-p-416, type 1, cl 3 federal specification single treatment response

#### **Thread Series Designator:**

Unc

#### Shelf Life:

N/a

### Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A500d0

# NSN 5305-00-271-3493

Machine Screw - Page 2 of 2

# Mil-std (military Standard):

Mil-s-6050 spec.

