## NSN 5305-00-271-5088

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-271-5088 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.808 inches **Fastener Length:** 0.875 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.337 inches and 0.343 inches **Head Height:** Between 0.211 inches and 0.216 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.216 inches Width Across Flats: Between 0.156 inches and 0.158 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch Material: Steel **Material Specification:** 66 federal standard single material response **Surface Treatment:** Zinc **Surface Treatment Specification:** Qq-z-325, type 2, cl 3 federal specification single treatment response **Thread Series Designator:** Unc **Specification Or Standard:** 1 type

Ttype

**Departure From Cited Designator:** 

As modified by thread size and series type designator

## NSN 5305-00-271-5088

Socket Head Cap Screw - Page 2 of 2



		ife:	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0