# NSN 5305-00-271-5216

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-271-5216



Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

Thread Length:

Between 0.350 inches and 0.469 inches

Fastener Length:

0.500 inches

**Head Style:** 

Fillister

Head Diameter:

Between 0.250 inches and 0.270 inches

**Head Height:** 

Between 0.106 inches and 0.113 inches

Hole Diameter:

0.046 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.164 inches

Hole Quantity:

1

Thready Qty Per Inch (tpi):

36

Min. Tensile Strength (psi):

125000 pounds per square inch

Hardness Rating:

Between 26.0 rockwell c and 32.0 rockwell c

### Screw Material:

Steel comp 8630

**Screw Material Specification:** 

Mil-s-6050 military specification single material response or an-s-9 military standard single material response

### Screw Surface Treatment:

Cadmium

### Screw Surface Treatment Specification:

Qq-p-416, type 1, cl 3 federal specification single treatment response

## Head Hole Configuration Style:

Round

**Thread Series Designator:** 

Unf

Shelf Life:

N/a

# NSN 5305-00-271-5216

Machine Screw - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-6050 spec.

