

NSN 5305-00-272-6373 Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-272-6373
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 1.190 inches and 1.560 inches
Fastener Length:
Between 2.690 inches and 2.750 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.550 inches and 0.562 inches
Head Height:
Between 0.368 inches and 0.375 inches
Hole Diameter:
0.064 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.375 inches
Width Across Flats:
Between 0.312 inches and 0.316 inches
Hole Quantity:
6
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
16
Min. Tensile Strength (psi):
170000 pounds per square inch
Hardness Rating:
38.0 rockwell c and 45.0 rockwell c
Minimum Yield Strength:

150000 pounds per square inch

Hole Configuration Style:

Round internal hexagon

Material:

Steel

Material Specification:

66 federal standard single material response

Surface Treatment:

Cadmium and chromate

NSN 5305-00-272-6373

Socket Head Cap Screw - Page 2 of 2



Surface Treatment Spec	ific	ation:
------------------------	------	--------

Qq-p-416 type 2 cl 3 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A003b0