## NSN 5305-00-273-2152

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-273-2152

| Thread Class:  |
|--|
| 2a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| Between 0.219 inches and 0.281 inches                                  |
| Fastener Length:   |
| Between 0.250 inches and 0.281 inches                                  |
| Head Style:  |
| Flat countersunk   |
| Head Diameter:   |
| Between 0.244 inches and 0.279 inches                                  |
| Internal Drive Style:  |
| Cross recess type 1  |
| Thread Diameter:   |
| 0.138 inches   |
| Thready Qty Per Inch (tpi):  |
| 32   |
| Min. Tensile Strength (psi):   |
| 60000 pounds per square inch   |
| Countersink Angle:   |
| Between 80.0 degrees and 82.0 degrees                                  |
| Screw Material:  |
| Steel  |
| Screw Material Specification:  |
| Qq-s-633 federal specification single material response                |
| Screw Surface Treatment:   |
| Cadmium  |
| Screw Surface Treatment Specification:                                 |
| Qq-p-416, type 2, cl 3 federal specification single treatment response |
| Thread Series Designator:  |
| Unc  |
| Specification Or Standard:   |
| 1 type and 2s style  |
| Departure From Cited Designator:                                       |
| As modified by fastener length   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |

No

## NSN 5305-00-273-2152

Machine Screw - Page 2 of 2



Fiig:

A500d0