

View Online at <https://aerobasegroup.com/nsn/5305-00-273-4533>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.235 inches and 0.265 inches

Fastener Length:

Between 0.485 inches and 0.515 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.105 inches and 0.119 inches

First Diameter From Head:

Between 0.041 inches and 0.046 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.220 inches and 0.280 inches

Internal Drive Style:

Slot

Thread Diameter:

0.060 inches

Thready Qty Per Inch (tpi):

80

Countersink Angle:

Between 80.0 degrees and 82.0 degrees

Externally Relieved Body Diameter Quantity:

1

Special Features:

Patch type or pellet type element in threads for self-locking feature

Material:

Steel comp 303

Material Specification:

Astm a582 assn standard single material response

Surface Treatment:

Oxide

Surface Treatment Specification:

Mil-c-13924 military specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.