

View Online at <https://aerobasegroup.com/nsn/5305-00-273-4533>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.235 inches and 0.265 inches

**Fastener Length:**

Between 0.485 inches and 0.515 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.105 inches and 0.119 inches

**First Diameter From Head:**

Between 0.041 inches and 0.046 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.220 inches and 0.280 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.060 inches

**Thready Qty Per Inch (tpi):**

80

**Countersink Angle:**

Between 80.0 degrees and 82.0 degrees

**Externally Relieved Body Diameter Quantity:**

1

**Special Features:**

Patch type or pellet type element in threads for self-locking feature

**Material:**

Steel comp 303

**Material Specification:**

Astm a582 assn standard single material response

**Surface Treatment:**

Oxide

**Surface Treatment Specification:**

Mil-c-13924 military specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-13924 spec.