
Socket Head Cap Screw - Page 1 of 2





Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 1.513 inches and 1.656 inches Fastener Length: Between 1.609 inches and 1.656 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.615 inches and 0.625 inches **Head Height:** Between 0.430 inches and 0.438 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.438 inches Width Across Flats: 0.312 inches Thready Qty Per Inch (tpi): 14 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 45.0 rockwell c **Minimum Yield Strength:** 130000 pounds per square inch Material: Steel **Material Specification:** 66 federal standard single material response Surface Treatment: Zinc Surface Treatment Specification: Qq-z-325, type 2, cl 3 federal specification single treatment response **Thread Series Designator:** Unc **Specification Or Standard:** 1 type **Departure From Cited Designator:** As modified by fastener length

NSN 5305-00-273-4950

Socket Head Cap Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

