## NSN 5305-00-273-4966

Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-273-4966



**Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 1.099 inches and 1.250 inches Fastener Length: Between 1.210 inches and 1.250 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.457 inches and 0.469 inches **Head Height:** Between 0.306 inches and 0.312 inches Hole Diameter: Between 0.044 inches and 0.050 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.312 inches Width Across Flats: Between 0.2500 inches and 0.2530 inches Hole Quantity: 6 Hole Type: Drilled Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 170000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c **Minimum Yield Strength:** 150000 pounds per square inch Hole Configuration Style: Round internal hexagon Material: Steel Surface Treatment: Cadmium and chromate **Surface Treatment Specification:** 

Qq-p-416 type 2 cl 3 federal specification single treatment response

## NSN 5305-00-273-4966

Socket Head Cap Screw - Page 2 of 2

**Thread Series Designator:** 

Unc

Specification Or Standard:

6 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

