## NSN 5305-00-273-5498

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-273-5498 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.575 inches **Fastener Length:** Between 0.609 inches and 0.641 inches **Head Style:** Pan **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.070 inches and 0.080 inches **Locking Feature:** Patch **Internal Drive Style:** Cross recess type iii **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch **Screw Material:** Iron alloy 660 **Locking Feature Material:** Plastic polyamide **Screw Material Specification:** Ams 5737 assn standard single material response or ams 5737 assn standard single material response **Locking Feature Material Specification:** Mil-s-18240 military specification single material response **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Bearing Surface Of Head Surface Finish:** 32.0 microinches **Thread Surface Finish:** 32.0 microinches

Unjc

**Thread Series Designator:** 

## NSN 5305-00-273-5498

Machine Screw - Page 2 of 2



Specification Data:
opeomodion bata.
80205-nas1742 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

Mil-std (military Standard):

Mil-s-18240 spec.

A500d0