# NSN 5305-00-273-6422

**Thread Class:** 

Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-273-6422



3a **Thread Direction: Right-hand Thread Length:** Between 1.508 inches and 1.750 inches Fastener Length: Between 1.690 inches and 1.750 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.921 inches and 0.937 inches **Head Height:** Between 0.616 inches and 0.625 inches Hole Diameter: Between 0.061 inches and 0.067 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.625 inches Width Across Flats: Between 0.500 inches and 0.505 inches Hole Quantity: 6 Hole Type: Drilled Thready Qty Per Inch (tpi): 11 Min. Tensile Strength (psi): 170000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c **Minimum Yield Strength:** 150000 pounds per square inch Hole Configuration Style: Round internal hexagon Material: Steel **Material Specification:** 66 federal standard single material response **Surface Treatment:** 

Cadmium and chromate

## NSN 5305-00-273-6422

Socket Head Cap Screw - Page 2 of 2



#### Surface Treatment Specification:

Qq-p-416 type 2 cl 3 federal specification single treatment response

#### Thread Series Designator:

Unc

Shelf Life:

N/a

#### Unit Of Measure:

---

### Demilitarization:

No

#### Fiig:

A003b0