
NSN 5305-00-273-7458

Socket Head Cap Screw - Page 1 of 2





Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.274 inches and 0.375 inches Fastener Length: Between 0.345 inches and 0.375 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.365 inches and 0.375 inches **Head Height:** Between 0.244 inches and 0.250 inches Hole Diameter: 0.047 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: Between 0.1875 inches and 0.2900 inches Hole Quantity: 3 Hole Type: Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 170000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c **Minimum Yield Strength:** 150000 pounds per square inch Hole Configuration Style: Round internal hexagon Material: Steel Surface Treatment: Cadmium and chromate **Surface Treatment Specification:**

Qq-p-416 type 2 cl 3 federal specification single treatment response

NSN 5305-00-273-7458

Socket Head Cap Screw - Page 2 of 2

Thread Series Designator:

Unf

Specification Or Standard:

6 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

