NSN 5305-00-274-0583

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-274-0583

Thread Class:
3a Thread Directions
Thread Direction:
Right-hand Thread Longth
Thread Length: 0.406 inches
Fastener Length: 1.750 inches
Head Style: Round extended washer
Head Diameter:
0.437 inches
Head Height:
0.101 inches
Extended Washer Diameter:
0.500 inches
Extended Washer Thickness: 0.028 inches
Internal Drive Style: Slot
Thread Diameter:
0.250 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
125000 pounds per square inch
Hardness Rating:
Between 26.0 rockwell c and 32.0 rockwell c
Screw Material:
Steel comp 8630 or steel comp 4037
Screw Material Specification:
Mil-s-6050 military specification 1st material response or ams 6300 assn standard 2nd material response
Screw Surface Treatment:
Cadmium or zinc
Screw Surface Treatment Specification:
Qq-p-416 federal specification 1st treatment response or qq-z-325 federal specification 2nd treatment response
Thread Series Designator:
Uns
Shelf Life:
N/a
Unit Of Measure:

NSN 5305-00-274-0583

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-6050 spec.