

View Online at <https://aerobasegroup.com/nsn/5305-00-274-1375>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.200 inches and 0.250 inches

**Fastener Length:**

Between 0.219 inches and 0.250 inches

**Head Style:**

Fillister

**Head Diameter:**

Between 0.166 inches and 0.183 inches

**Head Height:**

Between 0.069 inches and 0.079 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.112 inches

**Thready Qty Per Inch (tpi):**

40

**Min. Tensile Strength (psi):**

80000 pounds per square inch

**Screw Material:**

Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384

**Screw Material Specification:**

66 federal standard single material response

**Screw Surface Treatment:**

Plastic

**Screw Surface Treatment Specification:**

Mil-m-19833 type gdi-30 military specification single treatment response

**Thread Series Designator:**

Unc

**Specification Data:**

81348-ff-s-92 government specification

**Specification Or Standard:**

1 type and 4s style and 4-40 size

**Departure From Cited Document:**

As modified by surf. Treatment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A500d0

**Mil-std (military Standard):**

Mil-m-19833 spec.