NSN 5305-00-275-2759

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-275-2759

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.420 inches
Fastener Length:
Between 1.590 inches and 1.600 inches
Head Style:
Flat chamfer
Head Diameter:
0.750 inches
Head Height:
0.100 inches
Shoulder Diameter:
0.4985 inches first shoulder and 0.4990 inches first shoulder
Shoulder Length:
1.170 inches first shoulder and 1.180 inches first shoulder
Internal Drive Style:
Slot
Thread Diameter:
0.312 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
180000 pounds per square inch
Criticality Code Justification:
Aatn
Shoulder Shape:
Round first shoulder
Material:
Steel comp 4140
Material Specification:
Mil-s-5626, cond c military specification single material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416, type 2, class 3 federal specification single treatment response
Thread Series Designator:
Unif
Shelf Life:
N/a

NSN 5305-00-275-2759

Shoulder Screw - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.