NSN 5305-00-275-3446

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-275-3446 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.105 inches **Fastener Length:** 0.272 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.370 inches and 0.390 inches **Head Height:** Between 0.106 inches and 0.110 inches **First Diameter From Head:** 0.205 inches **Second Diameter From Head:** Between 0.220 inches and 0.224 inches **Third Diameter From Head:** 0.074 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.025 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.090 inches and 0.094 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: Between 0.165 inches and 0.169 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 Material: Steel comp 303se **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Thread Series Designator:**

Unc

NSN 5305-00-275-3446

Externally Relieved Body Screw - Page 2 of 2



She	lf	Life:	
Oile	••	LIIV.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0