Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-275-3446

| View Online at https://aerobasegroup.com/nsn/5305-00-275-3446 |
|--|
| Thread Class: |
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.105 inches |
| Fastener Length: |
| 0.272 inches |
| Head Style: |
| Flat chamfer |
| Head Diameter: |
| Between 0.370 inches and 0.390 inches |
| Head Height: |
| Between 0.106 inches and 0.110 inches |
| First Diameter From Head: |
| 0.205 inches |
| Second Diameter From Head: |
| Between 0.220 inches and 0.224 inches |
| Third Diameter From Head: |
| 0.074 inches |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter: |
| 0.025 inches |
| Distance From Largest Bearing Surface Of Head To End Of Second Diameter: |
| Between 0.090 inches and 0.094 inches |
| Distance From Largest Bearing Surface Of Head To End Of Third Diameter: |
| Between 0.165 inches and 0.169 inches |
| Internal Drive Style: |
| Slot |
| Thread Diameter: |
| 0.112 inches |
| Thready Qty Per Inch (tpi): |
| 40 |
| Externally Relieved Body Diameter Quantity: |
| 2 |
| Material: |
| Steel comp 303se |
| Material Specification: |
| Astm a582 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Thread Series Designator: |
| |

Unc

NSN 5305-00-275-3446

Externally Relieved Body Screw - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0