

View Online at <https://aerobasegroup.com/nsn/5305-00-275-8269>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.023 inches and 0.096 inches

Fastener Length:

Between 0.095 inches and 0.125 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.156 inches and 0.172 inches

Internal Drive Style:

Slot

Thread Diameter:

0.086 inches

Thready Qty Per Inch (tpi):

56

Min. Tensile Strength (psi):

55000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Screw Material Specification:

Mil-s-7720 military specification 1st material response or mil-s-7720 comp 303s military specification 2nd material response or qq-s-763 class 8 type a federal specification 3rd material response or qq-s-763 class 8 type a federal specification 4th material response

Screw Surface Treatment:

Passivate

Screw Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unc

Specification Data:

80205-nas662 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-7720 spec.